

# GP SERIES

## COMMERCIAL / RESIDENTIAL PORTABLE GENERATORS

### FEATURES:

- High performance alternator
- Steel fuel tank with incorporated fuel gauge
- Mobility kit with locking fold-down handles and never-flat wheels
- 1-1/4" diameter hardened steel tube cradle
- Hour meter with maintenance resets
- Circuit breaker protected outlets
- Low-tone muffler

### GP6500

Model 05623

Running Watts: 6500

Starting Watts: 8000



Ratings	
AC Rated Output	6.5kW / 6500 Watts
AC Maximum Output	8.0 kW / 8000 Watts
AC Voltage	120V/240V
AC Frequency	60 Hz
120 VAC Amperage	Rated 54.1/Max 66.6
240 VAC Amperage	Rated 27.0/Max 33.3
Engine	
Engine Type and Displacement	OHV Single Cylinder 389cc
Oil Capacity	1.1 Qt. (1.16 liter)
Low Oil Shutdown	Standard

Fuel	
Fuel Capacity	6.6 Gallons (24.98 liters)
Run Time @ 1/2 Load	9 Hours
Assembled Dimensions and Weight	
Dimensions L x W x H (inches)	33.5 x 26.5 x 27.5
Dimensions L x W x H (mm)	850.9 x 673.1 x 698.5
Unit Weight	185 lbs. (83.9 kg.)
Warranty	
Residential	2 Year Limited
Commercial	1 Year Limited

Outlets

4 x 5-20R



1 x L14-30R



Maximum wattage and current are subject to, and limited by, such factors as fuel Btu content, ambient temperatures, altitude, engine condition, etc. Maximum power decreases about 3.5% for each 1,000 feet above sea level; and will also decrease about 1% for each 6° C (10° F) above 16° C (60° F) ambient temperature.